

## tile specifications

style name	welcome II tile
style number	5T031
construction	needlebond hobnail
fiber	pet polyester
dye method	100% solution dyed

	english	metric
-----		
pattern repeat	none	
tufted weight	49.0	1,661.38 g/m <sup>2</sup>
gauge	1/12	47.24 per 10 cm
stitches per inch	11.0	43.31 per 10 cm
finished pile thickness	0.274	6.96 mm
total thickness	0.362	9.19 mm
average density	6477	12.06 kilotex
product size	24" x 24"	60.96 cm x 60.96 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments		


## testing

radiant panel	Class I
nbs smoke	less than 450
electrostatic propensity	less than 3.5 kv

## warranties

lifetime commercial limited

## installation method



## coordinating products

bon jour II tile, entree tile , welcome II, bon jour II

## environmental certification

nsf140 platinum  
cradle to cradle silver certified



Specifications are subject to nominal manufacturing variances.  
Material supply and/or manufacturing processes may necessitate changes without notice.



eco impacts

welcome II tile

end of life

recyclability

environmental guarantee

To recycle call 800.509.SHAW

100% recyclable

free pick up & recycling

materials

ingredients

face fiber

dye method

backing

does not contain PVC, phthalates, or PBD/PBDE

recycled content

total recycled content (by weight)

pre-consumer

post-consumer

bio-based/rapidly renewable content (by weight)

packaging

country of origin (manufacturer)

polyethylene terephthalate

100% dye injection print

polyolefin composite

53.9 %

27.0 %

26.9 %

0.0 %

100% recyclable

USA

Meets or exceeds all local and national regulations in country of manufacture.  
Manufactured in an ISO9001 & ISO14001 certified facility or equivalent.  
Recycled content is calculated using system allocation, mass balance, and direct insertion.  
The actual recycled content in this product will likely vary. For more information email [info@shawgreenedge.com](mailto:info@shawgreenedge.com).

third party certifications

MBDC cradle to cradle

NSF 140

CRI green label plus

USGBC LEED

silver certified

platinum certified

certified glp0520

contributes

Sustainability Through Innovation™ That's the Shaw Green Edge®